

TVS SMARTXONNECT™ TECHNOLOGY

With TVS Jupiter, we brought you the ZYADA KA FAYDA, and made it 'ZYADA' better with TVS Jupiter 125. The much-loved scooter now gets the most-advanced SmartXonnect™ variant with 60+ connected features to cater to the demands of today's urban commuting. With a perfect blend of futuristic, connected & practical features, TVS Jupiter 125 SmartXonnect™ is not just a scooter, it's a revolution on two wheels.



BENEFITS



BLUETOOTH® CONNECTED

Risk-free riding with hands-free accessibility.



CALL & SOCIAL MEDIA ALERTS

Always stay in touch with vour loved ones.



VOICE ASSIST

Command your scooter effortlessly. Just press the 'Voice Assist' switch, and let it lead the way!



TRAFFIC TIME SCREENS

Stav informed with real-time news, sports and weather updates.



DISTANCE-TO-EMPTY

Say goodbye to unexpected fuel stops with Distance-to-Empty (DTE).



AFE/IFE

Stav updated about your scooter's average mileage & instant fuel economy now on your SmartXonnect™ cluster.



ZYADA STYLE







ZYADA SPACE



LARGEST 33 L UNDERSEAT STORAGE









ZYADA SAFETY

FOLLOW-ME HEADLAMP NEW

The headlamp remains illuminated for 20 seconds even after the engine is turned off.



SIDE STAND ENGINE INHIBITOR

Automatically shuts off the engine when the side stand is engaged.



ZYADA CONVENIENCE



Distance-to-Empty, Average Fuel Efficiency, Sports, News and Weather updates.









Get car-like safety with turn-indicators which double up as hazard lamps providing enhanced visibility on the road. Now driving in foggy & rainy conditions has become safer.



ZYADA COMFORT









SMOOTH BODY BALANCE TECHNOLOGY MAKES THE VEHICLE EASIER TO CONTROL







ZYADA COLOURS







SPECIFICATIONS |

ENGINE (BS-VI compliant)

Type Single cylinder, 4-stroke, Air cooled

lacement 124.8c

Bore x Stroke 53.5 x 55.5 mr

Fuel Supply System ETFI-Fuel injection - Closed loop

ir Filter Type Paper filter

aximum Power 6.0 kW @ 6500 rpm aximum Torque 10.5 Nm @ 4500 rpm ansmission Type CVT automatic

ELECTRICALS

nition ECU-controlled ignition attery 12V, 4Ah MF battery

Headlamp LED with clear lens with MFR
Tail Lamp Bulb with LED light guide
Starting System Electric silent start

CHASSIS & SUSPENSION

me High rigidity underbone type

nensions (lxbxh) 1852 x 691 x 1168

'heelbase 1275 mi

Ground Clearance 163 mm (unladen

Seat Length 790 if Kerb Weight 108 k Fuel Tank Capacity 5.1 L Wheels Allow

ront Suspension --- Telescopic hydraul

Rear Suspension Monotube Inverted Gas (MIG) filled shock

with spring-aid 3-step adjustable

BRAKES & TYRES

ront 220 mm Disc ear 130 mm Drun

Tyre Size (Front & Rear) 90/90-12 54J (tubeless)

ALWAYS WEAR A HELMET WHILE RIDING







