

In case you need any Clarification or Service Assistance, please contact our Dealer

Dealer code , name
Address
Contact person name and mobile no. (Sales)
Contact person name and mobile no. (Service)
Email id

Or

TVS Motor Company's Area Offices (flip over for addresses)

Or

Toll Free Number: 1800-258-7111

Email: customercare@tvsmotor.com



CONTACT AT OUR AREA OFFICES

TAMILNADU-1

TVS Motor Company Limited V Floor, Gee Gee Universal.

No. 2, MC Nichols Road, Chetpet, Chennai - 600 031. Phone: 044-28361651/28361654 Email: AO.Chennai@tysmotor.com

TAMILNADU-2

2. TVS Motor Company Limited

No.10, 2nd floor, Shree Shanmugapriya Towers, Kannuswamy Street, Behind Hotel Annapoorna, R S Puram, Coimbatore - 641 002. Phone: 0422-4350060/2541035 Email: AO Coimbatore@tysmotor.com

TAMILNADU-3

3. TVS Motor Company Limited

D-09, Srinidhi Block, Agrini Apartments, Andalpuram, TPK Road,

Madurai - 625 003. Phone: 0452-4208690

Email: AO.Madurai@tvsmotor.com

TAMILNADU-4 & 5

4. TVS Motor Company Limited

No. 37, 1st Floor, Mian Road, West Brindavan, Near Hotel Le Royal Park, Puducherry - 605 103. Phone : 0413-2247655

Email: AO.Pondicherry@tvsomtor.com

KERALA

5. TVS Motor Company Limited

Ambady Towers, Second Floor, Door No. 27/631, A6, Edappally, Pookkattupady Road, Edappally PO., Cochin - 682 024. Phone: 0484-2544578/2556938 Email: AO.Cochin@tysmotor.com

ANDHRA PRADESH-1 & 3

6. TVS Motor Company Limited

No. D-19, 302, 3rd floor, Gayathri Arcade, Vikrampuri, Secunderabad - 500 003. Phone: 040-27840590/27844419 Email: AO.Hyderabad@tysmotor.com

ANDHRA PRADESH-2

7. TVS Motor Company Limited

Door No. 58-2-35, NCK Plaza, Near NTR Circle, Patamata, Vijayawada - 520 010. Phone: 0866-6575100 Email: AQ Vijayawada@tvsmotor.com

KARNATAKA-1

8. TVS Motor Company Limited

No. 600, Anand Surya, 2nd Floor, 15th Cross, 6th Phase, JP Nagar, Opp. BMTC Stop, Bangalore - 560 078.

Bangalore - 560 078. Phone : 080-26653433

Email: AO.Bangalore@tvsmotor.com

KARNATAKA-2 & GOA

9. TVS Motor Company Limited

No. 122/111 B, PDP Plaza, 3rd floor, New Cotton Market,

Karnataka Bank Road, Hubli - 580 029. Phone: 0836-4250617/4250618 Fmail: AO Hubli@tvsmotor.com



CONTACT AT OUR AREA OFFICES

MAHARASHTRA-1, 2 & 4

10. TVS Motor Company Limited No. 401, 4th floor,

The Chambers, Plot No. 4/12/3, Near Ganpati Chowk, Viman Nagar, Pune - 411 014. Phone: 020-26632111/26632110

Email: Service.pune@tvsmotor.com

MAHARASHTRA-3

11. TVS Motor Company Limited

Plot No. 206, House No. 241, Ward No. 73, 1st floor, West High Court Road, Dharampeth, Nagpur - 400 010.

Phone: 0712-2569932

Email: AO.Raipur@tvsmotor.com Service.Nagpur@tvsmotor.com

CHATTISGARH

12. TVS Motor Company Limited

No. 627-628, Magneto Offizo, Magneto the Mall, Labhandi, GE Road, Raipur - 492 010. Phone: 0771-4260006

Email: AO.Raipur@tvsmotor.com

MADHYA PRADESH-1

211-212. 2nd floor.

13. TVS Motor Company Limited

Chinar Incube Business centre, Chinar Fortune City, Near Vrindavan Dhaba, Hoshangabad Road, Bhopal - 462 026. Phone: 0755-2499406/2499306 Email: AO.Bhopal@tvsmotor.com

MADHYA PRADESH-2

14. TVS Motor Company Limited

301, 3rd floor, Shagun Arcade, Vijay Nagar circle, A B Road, Indore - 452 010. Phone: 9893028266

Email: AO.Indore@tvsmotor.com

GUJARAT-1 & 2

15. TVS Motor Company Limited

109, Ayana Complex, Opp. Suvarna Villa Bungalows, 100 ft Thaltej Hebbatpur road, Off : S.G. highway, Thaltej, Ahmedabad - 380 054. Phone: 079-65443748

Fmail · AO Ahmedahad@tysmotor.com

UTTAR PRADESH-EAST, CENTRAL & HILLS

16. TVS Motor Company Limited

1st floor, Cyber Tower, TC-34/V-2, Vibhuti Khand, Gomti Nagar, Lucknow - 226 010

Phone: 0522-4918300/4918301 Email: AO.Upe@tvsmotor.com

AO.upc@tvsmotor.com

UTTAR PRADESH-WEST

17. TVS Motor Company Limited

D-3 & D-4, 2nd floor, Sector - 10, Noida, Uttar Pradesh - 201 301

Phone: 011-29834640/29834773 Email: AO.Upw@tvsmotor.com

DELHI & HARYANA

18. TVS Motor Company Limited

D-3 & D-4, 2nd floor, Sector - 10, Noida, Uttar Pradesh - 201 301

Phone: 011-29834640/29834773 Email: AO.Delhi@tvsmotor.com AO.Harvana@tvsmotor.com



CONTACT AT OUR AREA OFFICES

PUNJAB, HIMACHAL PRADESH, JAMMU & KASHMIR

19. TVS Motor Company Limited

SCF- 10-11, Kalghaidhar Enclave, Baltana Road, Zirakpur, District Mohali - 140 603. Phone: 01762-511659/511661

Email: AO.Chandigarh@tvsmotor.com

RAJASTHAN-1

20. TVS Motor Company Limited

Plot No. 17-18 2nd floor of National Motors building, Jhotwara Industrial Area,

Jaipur - 302 012.

Phone: 0141-5150901/5150902 Email: AO.Jaipur@tvsmotor.com

RAJASTHAN-2

21. TVS Motor Company Limited

204, 2nd floor, Daulet Chambers, Near Meera Girls Collage, 4-D, Sardarpura, Udaipur - 313 004. Phone: 9001897479

Email: AO.Udaipur@tvsmotor.com

BIHAR

22. TVS Motor Company Limited

N-Plaza, Jamal Road, P.S. Kotwali, Patna - 800 001. Phone: 0612-2200068/2200069 Email: AO.BNJ@tysmotor.com

JHARKHAND

23. TVS Motor Company Limited

2nd floor, Lucas Building, Argora Bypass Road, Ranchi - 834 002. Phone: 0651-2244715

Email: AO.Ranchi@tvsmotor.com

ODISHA

24. TVS Motor Company Limited

#303, 3rd floor, Creative Plaza, Rasulgarh, Bhubaneshwar - 751 010. Phone: 0674-2580019

Email: AO.Bhubaneswar@tvsmotor.com

WEST BENGAL

25. TVS Motor Company Limited

Ground floor & First floor, 133 A.S.P. Mukherjee Road, Opp. Tollygunge Police Station, Kolkata - 700 026.

Phone: 033-24617092/24617096 Email: AO.kolkata@tvsmotor.com

NORTH EAST STATES

26. TVS Motor Company Limited

147, Udayan, Ganesh Guri, Opp. Punjab National Bank, R G B. Road

Guwahati - 781 005.

Phone: 0361-2202030/2202031 Email: AO.Guwahati@tvsmotor.com Dear friend,

Thank you for choosing the TVS Sport, India's strongest and most reliable motorcycle.

As a proud owner of TVS Sport, you are now a part of a family of millions of satisfied TVS customers.

TVS Sport are designed to deliver superior mileage and long-lasting performance. It also comes with refreshing looks.

This manual explains the features and operations of your TVS Sport. Please read it carefully and follow the instructions to enjoy years of safe riding.

To ensure reliable performance, we urge you to get your TVS Sport serviced only at TVS Motor Company Authorised Main Dealers / Authorised Dealers at specified regular intervals.

Happy Riding!

TVS MOTOR COMPANY LIMITED

This manual should be considered as a permanent part of the motorcycle and should remain with the motorcycle when resold or transferred to a new owner.

All information, illustrations, photographs and specifications contained in this owner's manual are based on the latest product information available at the time of this publication. TVS Motor Company Limited may, however, incorporate modifications or improvements on its vehicles at any time without notice, and therefore, in such events it is possible that the relevant part of the owner's manual does not apply to your vehicle.

Prior permission of TVS Motor Company Limited is required for quoting, copying or reproducing any part of this owner's manual.



Note

Accessories shown in the picture may not be part of the standard equipment.

Pictures shown in this manual are of TVS Sport Electric Start with Alloy Wheel model

Your motorcycle is provided with always glowing head lamp. The head lamp glows
automatically once the engine is started.

TVS Sport comes with 'SYNCHRONIZED BRAKING TECHNOLOGY - SBT*' which offers superior braking control. This new braking feature automatically activates front brakes whenever the rear brakes are used, thereby enhancing the braking performance of the vehicle. SBT assures more safety, reduces force required while braking and ensures lower changes of skidding.



* Applicable for SBT version only

Revision 3, Nov 2018

Operating this vehicle safely is an important responsibility of the rider. To help you make decisions about safety, we have provided operating procedure and other information in this manual. This information alerts you on potential hazards that could hurt you or others. Since it is not possible to warn you about all hazards associated with operating or maintaining the vehicle, you must use your own judgement.

You will find important safety information in following form in this manual. These words carry the following connotations:



Warning

Disregarding this message might result in injury to the rider.



Caution

This message indicates special procedures or precautions to be followed to avoid damage to the vehicle.



Note

This message provides further clarification for clearer understanding of any particular information.



Running-in information	01
Safe riding tips	02
Know your TVS Sport	07
Riding your TVS Sport	19
Maintenance	24
Warranty and services	47
Technical specifications	69
General information	72



The first 1000 km is a crucial part of your motorcycle. Proper running-in operation during this period helps in ensuring a **maximum life** and **smooth performance** of your motorcycle.

The reliability and performance of your motorcycle depends on the special care and restrain exercised during the running-in period. It is especially important that you avoid operating the engine in high speed (RPM), which could expose the engine parts to excessive stress. Recommended speed during the running-in is:

Maximum 50 kmph speed upto 1000 km (vary the engine speed for better mating of parts).

The first free service at $500 \sim 750$ km is most important. During running-in period all the engine components and other parts will have set in. All adjustments to be restored, all fasteners to be re-tightened. Engine cum transmission oil to be replaced. Timely performance of the first free service will ensure optimum service life and performance from the engine.



Caution

Replacing the engine cum transmission oil during first free service is most important for better life of engine. Always use TVS TRU4 PREMIUM oil (SAE 10W30 API-SL, JASO MA2) for better performance and life.

Since your motorcycle is fitted with Evaporative Emission Control System, **the motorcycle should not be laid on the floor during water wash.** Else it may lead to difficulty in starting and improper running of the motorcycle.



SAFE RIDING RECOMMENDATIONS

Any two wheeler riding requires some precautions to be taken to ensure the safety of the rider, pillion and other road users. These precautions are:

Familiarise yourself with new TVS Sport

Riding skill and your mechanical knowledge form the foundation of safe riding practices. We suggest you to practice riding TVS Sport in a low-traffic condition until you are thoroughly familiar with your vehicle and its controls. Remember practice makes you perfect.

Riding apparel

Loose, fancy clothing can be uncomfortable and unsafe when riding a two-wheeler. Choose good quality two wheeler riding apparel.

Know your limits

Ride within the boundaries of your own skill at all times. Knowing these limits and staying within them will help you avoid accidents.

A

Warning

Two wheeler safety starts with wearing a safety helmet of good quality. One of the most serious injuries that can happen is a head injury. Always wear ISI approved helmet. You should also have good suitable eye protection.



Posture

Proper vehicle riding starts with proper posture.

- Sit erect on the seat at the position which you feel most comfortable.
- 2. Keep your arms relaxed to give extra cushion for body on uneven road surfaces.
- Keep right arm and foot close to the brake lever and pedal, so as to enable fast action during panic braking.
- 4. Look widely instead of gazing at one point.
- Alter your sitting location/posture slightly at intervals during long rides. This will reduce fatigue.

Cornering

When cornering, centrifugal force works in a direction perpendicular to the direction in which the vehicle is moving. Centrifugal force increases in proportion with speed and the radius of the corner.

During cornering, reduce speed so as to reduce the effects of centrifugal force. By all means, avoid abrupt application of brakes or sudden steering.



Warning

One-hand riding is dangerous. Keep both hands firmly on the handle bar and both feet securely on the foot rest. Under no circumstances should both the hands be removed from the handle bar, as it is very dangerous.

Avoid use of mobile phones while riding as it could lead to fatal accident.

Do not downshift the gear in the midst of cornering. Slow down to a safe speed before negotiating a corner. If this is the first time you are riding a vehicle of this type, we suggest that you practice on a safe, open area to thoroughly familiarise with the operation of the vehicle.



Braking

For safe riding, it is very important to master the braking techniques.

- 1. Close/release the throttle.
- 2. Hold the vehicle upright as you apply the brake.
- 3. Progressive application of brake is safer.
- 4. Never depress the clutch lever while braking at higher speeds.
- 5. Apply both the brakes.
- Riding down hills, while cornering and wet roads, close throttle and down shift the gear to take advantage of gearbox and engine which acts as an additional brake. This will avoid the loss of control over the vehicle due to over speed.

Causes for poor braking

 If the brake shoes/pads or drum/disc are worn out or if there is water or oil on them, sufficient friction does not develop and brakes do not work well.

- Even when the brake works normally, if the road surface is wet or the tyre surface is worn-out, tyres do not take a firm hold on the surface, increasing the stopping distance.
- 3. Approximately 60% braking effect is from front brake. **Non-usage of front brake causes poor braking.**

A

Warning

As the vehicle speed increases, the stopping distance also increases progressively. Be sure that, you have sufficient distance between you and the vehicle or obstruction ahead of you.

Using only the front or rear brake is dangerous and can cause skidding and loss of control. Apply both the brakes together and with great care on a wet road or other slippery surfaces.

Any abrupt braking on slippery or irregular roads can cause loss of rider control.



ACCESSORY INSTALLATION AND SAFFTYTIPS

Use extreme caution while selecting and installing the accessories for your motorcycle.

The addition of unsuitable accessories can lead to unsafe operating conditions. Your friendly Dealer will assist you in selecting quality accessories and installing them correctly.

While selecting the accessories, make sure the accessories **should not obstruct lighting**, **steering**, **suspension level and ground clearance**. Please ensure that, if the tank cover is used, it is not getting en-trapped between fuel tank and fuel tank cap.

Additional electrical equipments and controls should not exceed the specified electrical system load of the vehicle (capacity of the battery and magneto).

EMISSION CONTROL

Exhaust emission control system

All the TVS vehicles are tested in the factory for optimum fuel efficiency and CO levels.

Do not disturb the Carburettor settings as this may lead to higher fuel consumption and also higher CO levels.

If the vehicle needs any adjustments, please consult nearest TVS Motor Company Authorised Main Dealer or Authorised Dealer

While adequate care is exercised at the factory to ensure that the emissions are within the limits, it is essential for the owner to always maintain the motorcycle in good condition by getting it periodically checked and serviced by TVS Motor Company Authorised Main Dealer or Authorised Dealer so that the emission and fuel consumption levels are maintained as per norms.

①

Note

Your vehicle is tested and certified for emission which meets BS IV emission norms and is valid for initial 12 months from the date of purchase. Get your vehicle certified by the Government authorised emission testing station every year (after initial 12 months of usage).



Crankcase emission control system

The engine of TVS Sport is equipped with a closed crankcase system to prevent discharging crankcase emissions into the atmosphere. Blow-by gas is returned to the combustion chamber through the air cleaner and the carburettor.

Evaporative Emission Control System

The TVS Sport is equipped with an evaporative emission control system which consists of a canister and associated piping. This system prevents the escape of fuel vapors from the fuel tank

A

Warning

If there is any abnormal jerk, startability issue are felt in the vehicle or noise due to sudden escape of gas during opening of fuel tank cap, immediately report to the TVS Motor Company Authorised Main Dealer/Authorised Dealer.

VEHICLE IDENTIFICATION NUMBER

Serial numbers of both frame and engine are required for vehicle identification. They are also required to assist your Dealer for operating parts or referring to special information.



The frame serial number is stamped on the right side of the steering head tube.





In KS model, the engine serial number is stamped on the top surface of left side crankcase. In ES model the engine serial number is stamped on the front surface of left side crankcase.

Frame number								
Engine number								_
Control key numb	oer							

Please fill the above boxes now for future reference



CONTROLKEY

TVS Sport comes with a pair of identical control keys. These keys are to operate ignition cum steering lock, fuel tank cap and seat lock.

IGNITION CUM STEERING LOCK

There are three positions in the ignition cum steering lock. They are:

1. 'OFF' position


All the electrical circuits are turned 'OFF' in this position. Engine will not start. Key can be taken out.

2. 'ON' position

In this position, all the electrical circuits are turned 'ON' and the engine can be started now. Key cannot be removed in this position.

3. 'LOCK' position

TVS Sport steering can be locked in both 'left' and 'right' directions. To lock the steering, turn the handle bar all the way to the 'left' or 'right'. Push the key in and turn it to the 'LOCK' position and take out. All the electrical circuits are turned 'OFF' in this position.



Insert the key into the lock and turn it to 'OFF' or 'ON' Position to unlock the steering.

A

Warning

Never attempt to move the vehicle when the steering is locked, you may lose balance.



Caution

Leaving the ignition cum steering lock in 'ON' position will drain battery when the vehicle is not in use. So "Switch off" and take the key out when the vehicle is not in use.



SPEEDOMETER ASSEMBLY

1. Speedometer


Indicates the vehicle speed in kilometers per hour.

2 Odometer

Registers and displays the total distance covered by the vehicle in kilometers. The last digit denotes one tenth of a kilometer.

3. Fuel gauge

Fuel gauge indicates the approximate quantity of fuel available in the fuel tank. Once the fuel indication is in red band (marked in the dial) re-fill the fuel as soon as possible.



4. Economy and power mode indicators

Economy indicator (green lamp) indicates that the vehicle is running in economy mode which gives better fuel economy.

Power indicator (amber lamp) indicates that the vehicle is running in power mode which results in reduced fuel economy.

5. Turn signal indicator lamp

Flashes when the 'left' or 'right' side turn signal indication is activated.

6. High beam indicator lamp

Glows when the head lamp high beam is activated.

7. Neutral indicator lamp (N)

Glows when the vehicle is in neutral and goes 'OFF' if the gear is shifted from neutral.



Note

Always ride in 'economy mode' for better fuel efficiency. If the vehicle is kept idle for more than 20 seconds, the power mode indicator blinks and informs you that the fuel is getting wasted and the engine needs to be switched 'OFF' to save fuel.



HANDLE BAR LEFT SIDE

1. Beam control switch

The head lamp glows automatically along with the speedometer back illumination and tail lamp once the engine is started. Only the head beam (high/low) can be controlled by pressing the beam control switch.

Press the switch towards ' $\equiv \square$ ' to turn-on the head lamp high beam or press the switch towards ' $\equiv \square$ ' to turn-on the head lamp low beam.

2. Pass by switch

Press the switch to flash the head lamp high beam. It is used to give signal to the vehicles coming from opposite direction while overtaking other vehicles during day. If the switch is pressed while the head lamp glowing in high beam, there will be no change in the head lamp beam.

Note

Once the engine is started the head lamp, speedometer back illumination and tail lamp glows automatically. Only head lamp beam (high/low) can be controlled using beam control switch.



3. Clutch lever

Use the clutch lever to disengage the drive to the rear wheel while shifting the gears. Squeezing the lever towards grip disengages the drive.



Warning

Use appropriate head lamp beam 'high/low' as per the traffic and road conditions for your safety and to avoid inconvenience to other riders. It is strongly recommended to ride the vehicle in 'low beam' during day.

4. Turn signal lamp switch

Slide the turn signal lamp switch to left ' ' to operate respective turn signal lamps (LH/RH). Press the knob to turn 'OFF'.

5. Horn switch

Press the switch ' ' to operate the horn.

6. Choke lever

Pull the choke lever towards left to apply choke. During cold start, apply the choke and start the vehicle using electric starter or kicklever without opening / with less opening of throttle. Once the engine is started and running in stable RPM, release the choke and ride the vehicle.

A

Warning

Always use the appropriate turn signal lamps when you intend to change lanes or take turns. Be sure to switch 'OFF' the turn signal lamps after negotiating the turns or lanes.





Caution

Always use choke for starting the cold engine. Never open the throttle fully when the choke is applied. It may lead to flooding of engine and difficulty in starting.

HANDLE BAR RIGHT SIDE

1. Flectric start switch*

When the transmission is in neutral, just press the electric starter switch ' (3)' to start the engine electrically. Else, depress the clutch lever and press the starter switch to start.







Caution

For cold starts, avoid using electric starter. Use kickstarter. A typical example is early morning start. This would reduce load on the battery and prevents quick drain.

2. Throttle grip

Engine speed is controlled by the rotation of the throttle grip. Twist it towards you to increase the engine speed and away from you or release it to decrease the engine speed.

3. Front brake lever

The front brake is applied by squeezing the front brake lever gently towards the throttle grip. The brake lamp glows on application of front brake.

FUEL TANK* CAP

To open the fuel tank cap, move away the protection lid (A) from its position. Insert the key into the lock and turn it in clockwise. The tank cap ejects automatically. Take out the cap along with the key.

To close, press the cap back to its original position by keeping the front end (arrow marked) towards handle bar. Take out the key and close the production lid.





Warning


Avoid spilling of fuel on the hot engine. Never refill fuel near open flame. Do not smoke while refueling. Do not use cell phones while refueling.

^{*} Fuel tank is not a measuring instrument and capacity of the fuel tank may slightly vary from the indicated capacity.



EVAPORATIVE EMISSION CONTROL SYSTEM

This vehicle is fitted with Evaporative Emission Control System (EVAP). If there is any abnormal jerk, startability issue are felt in the vehicle or noise due to sudden escape of gas during opening of fuel tank cap, immediately report to the TVS Motor Company Authorised Main Dealer / Authorised Dealer





Do not clean the vehicle by laying down on floor, to avoid fuel entry into EVAP system.




Caution

Never fill fuel beyond the fuel tank inlet (1). Filling above the inlet may result in improper breathing of fuel tank which leads to difficulty in starting as well as improper running of the vehicle. Whenever refueling the bike fill only the recommended quantity of fuel (10 liters including 2 liters reserve).

FUEL COCK

Fuel cock has the following three positions:



KNOW YOUR TVS SPORT



ON: Fuel flows in this position when the fuel

RES: Switch over the fuel cock lever to this position when the fuel stops flowing in 'ON' position.

 OFF: Fuel flow cuts off from the fuel tank to carburettor.

Caution

Leaving the fuel cock in 'ON' or 'RESERVE' position may cause the fuel tank to completely drain out, incase any malfunctioning of carburettor float system.

Similarly, if the fuel cock is positioned between 'ON' and 'OFF' may drain off entire fuel while riding the vehicle

KICKSTARTER LEVER

The kick starter lever is located on the right side of the vehicle.

To start the vehicle, keep the ignition in 'ON' condition and transmission in neutral. Keep your foot on the lever extension and kick from top and stroke to bottom with rapid motion.

Please note that the engine can be started with the kickstarter lever only when the vehicle is in neutral.






GEAR SHIFT LEVER

TVS Sport has a heel and toe gear shift lever. To shift the gear from neutral to higher, press the rear end of gear shift lever by heel once for each gear after applying the clutch.

Similarly, to down shift to lower gears, press the front end of the lever by toe once for each gear after applying the clutch.



REAR BRAKE PEDAL

Rear brake pedal is located on the right side of the vehicle. Press the rear brake pedal with your right foot to apply the rear brake. The brake lamp glows on application of brake.



Marning


Brakes are items of personal safety and should always be maintained in proper condition.



CENTRE STAND AND SIDE STAND

TVS Sport is equipped with a centre (1) and side stand (2).

To place the vehicle on centre stand, hold the handle bar left grip with left hand and pillion handle with right hand. Place your foot firmly on the centre stand extension (1a) and press with adequate effort. Ensure both the legs of centre stand are touching the ground before placing the vehicle on the stand. Side stand can be operated by sitting on the vehicle with your left foot by pushing it away from the vehicle till it stops.





Warning

Always release the side stand to its full up position before moving the vehicle.



Caution

Never sit on the vehicle when it is supported by stand. Always park the vehicle on a flat, firm surface.

COVER FRAME L



Open the cover frame L in the following manner to access the battery assembly.

- 1. Remove the mounting screws (A) & (B) from the front and rear mounting of the cover frame.
- 2. Gently pull out the front end (C) of the cover frame from fuel tank cushion
- 3. Carefully dislocate the cover frame lugs from the cover seat tail and take out the cover frame.

Reassembly

- Locate the lugs provided at the rear end of the cover frame to the location provided of the cover seat tail
- 2. Gently press the lug provided in the front (C) of the cover frame into the fuel tank cushion
- 3. Assemble the screws (A) & (B) and tighten.

Caution

While reassembling the cover frames, see that the rubber cushions provided for the cover lugs are in place.

SEAT LOCK

Seat lock is provided at the tail end of the vehicle to open the seat assembly and there by accessing the tool kit and first aid kit

To open the seat assembly,

- Insert the control key into the seat lock and rotate it in clockwise direction
- 2. Take out the seat assembly by lifting it from the rear end and gently tapping it on the front end.

For reassembling,

Assemble the seat in the frame and push it forward





2. Gently press at the rear end until you hear a click sound and take out the control key.

TOOL KIT AND FIRST AID KIT

To assist you in performing certain aspects of maintenance and emergency repairs, a tool kit is supplied along with the vehicle and is located below the seat assembly.

A first aid kit is available below the seat assembly at the location shown in the figure. Remove the seat assembly as explained earlier to access the tool kit and first aid kit.





The tool kit consists one number each of the following:

- 1. 14x17 mm open end spanner
- 2. 10x12 mm open end spanner
- 3. Combination screw driver bit
- 4. Screw driver handle
- 5. Tool bag



Note

It is recommended to use the tool kit in case of any emergency only. It is always advisable to take your vehicle to TVS Motor Company Authorised Main Dealer / Authorised Dealer.



INSPECTION BEFORE RIDING

Check the following items before riding.

ITEM	WHAT TO CHECK FOR
Engine cum transmission oil	Availability of oil upto the level (page no. 31)
Fuel	Enough fuel for the planned distance of running
Tyres	Correct pressure (page no. 39)
	Adequate tread depth / No cracks or cuts
Battery	Proper working of horn, brake lamp, turn signal lamps, neutral lamp, fuel gauge and electric starter*.
	Electrolyte level (page no. 28)
Lighting	Proper working of head lamp high beam / low beam, high beam indicator in speedometer, speedo lamps and tail lamp.
Steering	Smooth movement / No play or looseness
Throttle	Correct free play of cable / Smooth operation
Clutch	Correct free play of cable (page no.31) / Smooth and progressive action
Brakes	Correct lever and pedal play (page no. 34)
Wheels	Free rotation

^{*} Applicable for electric start model only



STARTING THE ENGINE

Turn the fuel cock lever to the 'ON' or 'RESERVE' position based on the availability of fuel in the tank. Insert the control key into the ignition cum steering lock and turn it to the 'ON' position.

Keep the transmission in neutral and press the electric starter switch* to start the engine electrically or kick start.

When the engine is cold

- Pull the choke lever and start the engine using kick starter with no opening / very less opening of throttle.
- Once the engine is started and running stable, release the choke lever and ride the vehicle (when the engine is worm/hot don't use choke).

Caution

Do not keep the engine in idling rpm for long and do not open excessive throttle when engine is idling and the vehicle is parked. It leads to overheating of engine and damage to the internal components.

* Applicable for electric start model only



Warning

Do not run the engine indoors where little or no ventilation available. Exhaust gases are extremely poisonous.

SETTING THE VEHICLE IN MOTION

- 1. Depress the clutch lever and engage the first gear by pressing rear end of gear shift lever.
- 2. Open the throttle slowly and simultaneously release the clutch lever gently and gradually. The vehicle starts moving forward.
- 3. As the vehicle picks up speed, shift to the next higher gear by closing the throttle, applying the clutch and pressing the gear shift lever rear end once again.
- Release the clutch lever and open the throttle smoothly. Select the required gear in similar manner

Using the transmission

The transmission is provided to keep the engine to run smoothly in its normal operating speed range. The gear ratios have been carefully chosen to meet the characteristics of the engine.



The rider should always select the most suitable gear to achieve the necessary speed and pulling power smoothly.

Riding on hills / gradients

When climbing steep hills, the motorcycle may begin to slow down and show lack of power. At this point you should shift to a lower gear so that the engine will again be operating in its normal power range. Shift gears rapidly to prevent the motorcycle from losing momentum.

When riding down a hill, the engine may be used as brake by shifting to a lower gear.

Stopping and parking

- 1. Close the throttle completely and apply both the brakes simultaneously.
- 2. Down shift the gears as the road speed decreases. Bring the engine to neutral position just before the vehicle stops.

Marning

Reduce speed to a safe limit before turning / cornering. Do not apply brake while turning / cornering. Do not disengage clutch before braking.

- 3. Turn the ignition 'OFF'.
- 4. Park the vehicle on a firm, flat surface.
- 5. Lock the steering and turn 'OFF' the fuel cock.

FUEL RECOMMENDATION

Use BS IV/unleaded petrol only.

The petrol should be 85 to 95 octane by research method. Use recommended fuel additives for longer life of engine components and lower maintenance. Petrol mixed with ethanol will have impact on engine components. Contact your TVS Motor Company Authorised Main Dealer / Authorised Dealer for usage.

Caution

Never mix oil in petrol in the fuel tank. Always fill fuel from the reputed and reliable fuel stations.

Note

Use fuel additives in petrol as recommended by the respective manufacturer for low carbon deposition.



CHECKS AND TIPS FOR IMPROVING FUELECONOMY

Regular checks

Carry out the periodic maintenance checks as specified in this manual (refer page no. 25 and 26). Regular maintenance checks will save fuel and ensure trouble-free, enjoyable and safe riding besides keeping the environment clean.

Spark plug

A dirty or defective spark plug leads to wastage of fuel due to incomplete combustion. Clean and adjust the spark plug only if necessary. **Replace the spark plug every 12000 kms (1 year). Always use recommended spark plug only.**

Air cleaner element

A dirty air filter element restricts airflow and increases fuel consumption. Inspect and clean the element periodically. Replace the element every 12000 kms.

Clutch

Increase in engine rpm during acceleration, without increase in road speed indicates the clutch slip.

A slipping clutch will cause high fuel consumption and engine over heat. If the condition persists even after adjusting the clutch lever play, immediately have the clutch checked by TVS Motor Company Authorised Main Dealer or Authorised Dealer.

Engine cum transmission oil

Dirty or less engine cum transmission oil increases the friction between various parts of engine and reduces the engine life, thereby increases the fuel consumption. Regularly inspect the engine cum transmission oil for correct level and top-up if necessary. Get it replaced at regular intervals as per the maintenance schedule.

Carburettor and air cleaner assembly Check and ensure the fitment and tightness of carburettor, pipe intake and air cleaner. Any loose assembly leads to starting trouble and low fuel economy.

Caution

Never drive the vehicle with half clutch. This will reduce the life of clutch and affects the performance of the vehicle and fuel economy.



Fuel leak

Check and arrest fuel leak if any, from tank, carburettor and fuel lines. Loss of fuel due to leak may drain the fuel tank completely.

Tvres

Low tyre pressure has adverse effect on the vehicle. The **drag on the vehicle** increases resulting decreased fuel economy. Further more, handling may be adversely affected. Check the tyre pressure regularly and inflate to the recommended pressure (refer page no. 39). Never use tyres which are worn beyond the permissible limit.

Chain slackness

Check and ensure drive chain slackness. Excess slackness leads to higher fuel consumption (refer page no. 41).

Wheel freeness

Check and ensure the wheel freeness by rotating the wheels at least once in a week to avoid wastage of fuel.

Fast starting from rest wastes fuel

A racing start from rest at full throttle can waste fuel and damage the engine. It also creates a potentially dangerous traffic situation.

Fast acceleration wastes fuel

Fuel is wasted whenever you suddenly accelerate or apply brake.

Avoid unnecessary idling

While waiting for someone or stopping in signals for long time, if the engine is kept running at idle speed, it causes unnecessary wastage of fuel.

Avoid frequent braking

Anticipate corners and slopes as well as the traffic conditions. **Unnecessary frequent braking will reduce the fuel economy.**

Economy mode

Always ride the vehicle in economy mode for better fuel efficiency.



Note

The on-road mileage of TVS Sport is dependent on several factors like Road condition, Quality of fuel, Riding speed, operation of Clutch and Brake, Tyre inflation, Maintenance / timely servicing of vehicle, load etc.. and hence will differ from the mileage given under standard test conditions such as made in recognised institute like ARAI.



MAINTENANCE SCHEDULE

The maintenance schedule indicates the intervals between periodic services. At the end of each interval, be sure to inspect, check, replace, adjust, lubricate and service as instructed. If the maintenance is not done periodically, it will result in rapid wear and severe damage to the vehicle. If the vehicle is used under high stress conditions such as continuous full throttle operation or if used / operated in dusty climate, certain jobs should be performed more often to ensure reliability of the vehicle. Cylinder head, steering components, suspension, chain and wheel components etc., are key items and require very special and careful servicing. TVS Motor Company Limited strongly recommends that the jobs as per the maintenance schedule be performed by your TVS Motor Company Authorised Main Dealer / Authorised Dealer.

Periodic inspections may reveal one or more parts that may need replacement. Whenever replacing parts on TVS Sport, it is recommended that you use only the **TVS Motor Company Genuine** parts.



Caution

Proper running-in and maintenance are mandatory for making certain that your vehicle is reliable and gives optimum performance at all times. Be sure that the periodic maintenance is performed thoroughly in accordance with the instructions given in this owner's manual.

In more dusty areas, the air filter element may required early replacement than the mentioned kilometers to avoid costly damages to the engine.



PERIODIC MAINTENANCE SCHEDULE (months or km whichever occurs earlier)

Item		In free	service		After free service		
Service km Period from date of sale	1st 500-750 1 month		3rd 5000-6000 6 months	4th 8500-9000 9 months	Every 3000 km	Every 6000 km	Remarks
Engine cum transmission oil	R	R	R	R	R	-	
Oil filter (strainer)	С	С	С	С	С	-	
Centrifugal filter	-	-	С	-	-	С	
Spark plug	C & A	-	-	-	-	-	Replace every 12000 km
Air cleaner element ¹	1 & C	1 & C	1 & C	1 & C	1 & C	-	Replace every 12000 km
SAI filter element	I	-	-	-	-	-	Replace every 12000 km
PCV filter element	-	-	-	-	-	-	Replace every 12000 km
Carburettor assembly	C & A	-	-	-	-	-	C & A every 12000 km after first service
Tappet clearance	1 & A	-	1 & A	-	-	1 & A	
Fuel cock sediment bowl	С	С	С	С	С	-	
Hose fuel with respective clamps	I	1	I	I	I	I	Replace every two years (or) 20000 kms
All control cables ²	I, A & L	I, A & L	I, A & L	I, A & L	I, A & L	-	
Throttle grip	-	-	L	-	-	L	Lubricate using grease
Choke operation	ı	ı			I	-	
Steering smooth operation / play	1 & A	1 & A	1 & A	I & A	1 & A	-	C & L with fresh Bechem premium grade 3 grease every 12000 km
Front fork oil	-	-	-	-	-	-	Replace every 18000 km
Front and rear suspension	- 1	ı			- 1	-	Inspect for proper functioning
Speedometer gear pinion / cable	-	-	L	-	-	L	Lubricate using grease
All fasteners	1 & TI	I & TI	I & TI	I & TI	I & TI	-	
Drive chain	C, L & A	C, L & A	C, L & A	C, L & A	C, L & A	-	Adjust if necessary



Item		In free	service		After fre	e service	
Service km Period from date of sale	1st 500-750 1 month		3rd 5000-6000 6 months		Every 3000 km	Every 6000 km	Remarks
All bulbs, horn and switches	I	I	I	1	I	-	Inspect for proper functioning
Head lamp beam	1 & A	1 & A	1 & A	1 & A	1 & A	-	
Battery electrolyte level	1 & T	1 & T	1 & T	1 & T	1 & T	-	
Specific gravity and voltage ³	I	I	I		I	-	
Brake effectiveness / play4	1 & A	1 & A	1 & A	1 & A	1 & A	-	
Brake cams / SBT system parts*	-	-	C & L	-	-	C&L	Lubricate using grease
Wheel freeness		- 1			I	-	
Wheel spokes	I & TI	-	I & TI	-	-	I & TI	Only in spoke wheel model
Tyre pressure in cold condition	1 & S	1 & S	1 & S	1 & S	1 & S	-	
Engine Idling speed	1 & S	1 & S	1 & S	1 & S	1 & S	-	
Idling CO% ⁵	1 & S	_	-	-	-	-	
Centre / side stand pivot	L	L	L	L	L	-	Lubricate using TRU4 oil
Kick starter pedal pivot	L	L	L	L	L	-	Lubricate using TRU4 oil
Swing arm bearings	-	-	-	-	-	_	Lubricate using grease every two years
Evaporative emission control system	I	I	I	I	I	_	Check for intactness of hoses and canister
Fuel tank assembly**	1 & C	1 & C	1 & C	1 & C	1 & C	_	·

R - Replace; I - Inspect; T - Top up; C - Clean; A - Adjust; L - Lubricate; TI - Tighten; S - Set

¹ Inspect for any damage ² Inspect for proper operation and adjust play. Lubricate ends using grease.

³ Recharge if necessary ⁴ Lubricate brake pedal shaft every service using TRU4 oil

⁵ Idling CO% should be set with the help of exhaust gas analyser and tachometer only

^{*} Applicable for SBT version only ** Check for abnormal vehicle jerk / noise while opening the cap / leak. If found any, contact TVS Motor Company Authorised Main Dealer or Authorised Dealer.



RECOMMENDED LUBRICANTS

Application	Qty	Manufacturer	Brand
Engine cum transmission oil	900 ml (after draining)	TVS Motor Company	TVS TRU4 PREMIUM oil
	1000 ml (after disassembly)		(SAE 10W30 API-SL, JASO MA2)
Front fork oil	155 ± 2 ml / leg (GIL make)	IOC / Castrol	Teleshockab oil
	$157 \pm 2 \text{ ml / leg (TOP make)}$		
Grease	_	Bharath petroleum	MP Grease no. 3
		IOC	Servo Gem no. 3
		Bechem	Bechem premium grade 3
Chain lubricant	_	TVS Motor Company	TRU SPRAY
Fuel additives	As recommended		IFTEX



SELF - MAINTENANCE PROCEDURES BATTERY

Battery is located below the cover frame L. The electrolyte level of the battery must be maintained to avoid damages to the battery. To check the electrolyte level, follow the procedure:

- Place the vehicle on centre stand on a flat surface and open the cover frame L as explained in page no. 16.
- 2. Inspect the battery electrolyte level. It should be between the minimum and maximum level.



- 3. If the electrolyte level is below minimum level, add only distilled water upto the maximum level by removing the filler caps.
- 4. Reinstall the filler caps and clean the battery thoroughly, apply petroleum jelly to the battery terminals to protect it from corrosion.

Incase of any abnormality or for removal of battery from the vehicle, contact TVS Motor Company Authorised Main Dealer or Authorised Dealer.



Caution

Once the battery is charged initially, never add diluted sulphuric acid. Use only distilled water for topping up. Never add tap water.

Never check the battery charge by shorting the terminals. Always connect the positive terminal first and then negative to avoid sparking.


Do not obstruct, bend or change the routing of battery air vent tube. Make sure that the vent tube is firmly attached to the battery and the other end is open and clear.




FUSE REPLACEMENT

Non-working of electrical systems may be due to safety fuse failure. Short circuit or overload in the electrical system are the main causes for fuse failure. Follow the procedure given below for inspecting and replacing the fuse.

- Open the cover frame L as explained earlier (refer page no. 16).
- 2. The fuse case fitted on the battery band contains a 10 A fuse.
- 3. Pull out the fuse case from battery band.
- 4. Open the fuse case and slide out blown fuse.





- 5. Replace the fuse with a new (extra fuse is provided inside the fuse case itself).
- 6. Close the fuse case and re-fix it into the battery band
- Turn 'ON' the ignition switch and check for proper functioning of electrical systems. Incase the fuse fails again, consult the nearest TVS Motor Company Authorised Main Dealer / Authorised Dealer.

•

Caution

Do not use vehicle by **shorting the wires without a fuse.** This may result in overheating of electrical/wiring and may result in fire.

Do not use fuse of higher amperage than specified for the safety of electrical system.



SPARK PLUG

- 1. Clean the dust and mud around the spark plug mounting to avoid falling inside the cylinder.
- 2. Pullout the suppressor cap from spark plug. Using spark plug spanner, remove the spark plug.

A spark plug with heavy carbon deposits will not produce strong sparks. Hence, only if necessary, remove the carbon deposits from the spark plug with a small wire brush or spark plug cleaning tool.

0.6 ~ 0.8 mm

Inspect the spark plug electrodes (A) and (B) for any corrosion. If found any replace the spark plug with new

Inspect the spark plug gap with a wire gauge / feeler gauge. Readjust the spark plug gap to **0.6~0.8 mm** if required.

After cleaning and adjusting the gap, reinstall the spark plug and tighten by hand to avoid cross threading. Finally tighten using the spanner. Do not over tight or cross thread the spark plug.



Caution

Always use only recommended make and type of spark plug. **Replace spark plug every 12000 km.**

Cover the spark plug hole with cloth when the plug is removed to prevent dust/water entry.

It is advisable to tight the new spark plug by hand till the end and then loose and again re-tight the spark plug by 1/8 of rotation after sealing by using only the hand tool.



ENGINE CUM TRANSMISSION OIL

Check the engine cum transmission oil level periodically.

- Place the vehicle on centre stand on a flat surface. Wipe-off the surroundings of gauge oil level
- 2. Remove the gauge oil level and wipe it clean.
- 3. Fix the gauge back to its mounting hole. Do not thread in
- 4. Take out the gauge and check the oil level.
- 5. The oil level should be between minimum and maximum level marks of the gauge as shown in the figure.



- If the oil level is less than the minimum level, add TVS TRU4 PREMIUM oil (SAE 10W30 API-SL. JASO MA2) upto the maximum level mark.
- 7. Wipe out the oil traces with a clean cloth to prevent dust accumulation and assemble back the gauge oil level.



Caution

If the vehicle is driven with less engine cum transmission oil, engine components will be severely damaged. Check the oil level as per the schedule to avoid costly damage.

Do not fill excess oil, it may cause oil leak. Always use TVS TRU4 PREMIUM oil (SAE 10W30 API-SL, JASO MA2) only.

CLUTCH ADJUSTMENT

Clutch lever free play is one of the most important adjustment which you may need to check in-between services for better life of the clutch plates.


MAINTENANCE

The free play of the clutch lever should be 10 ~ 15 mm as measured at the clutch lever end before the clutch begins to disengage.

Adjust the clutch lever free play periodically by means of clutch cable adjuster at arm clutch release if the free play is not within the specified limit.

- 1. Ensure that the engine is cold.
- 2. Loosen the lock nut (2) while holding the clutch cable adjuster (3). Adjust the clutch cable adjusting nut (1) 'in' or 'out' to give sufficient play in the lever.





3. After adjusting the play, hold the adjuster nut in the same position, tighten the lock nut.



Caution

Too much or too less clutch lever free play will damage the clutch plates, thereby affecting the performance of the vehicle.

Adjust the clutch lever free play only when the engine is cold.




REAR SHOCK ABSORBERS

TVS Sport is provided with 5 step adjustable rear shock absorbers to meet different road and load. There are 5 notches for adjusting spring load.

If the spring is adjusted to the minimum notch, then the shock absorber will be softer which is good for light loads. If the spring is adjusted to maximum notch, then it will be stiffer which is good for heavy loads.

Adjust the spring pre-load by shifting the adjuster to the required notch according to the different load conditions. The more you compress the spring, the suspension becomes more stiff.







Keep both left and right shock absorbers spring adjusters in the same position.



BRAKES

Front brake

- 1. Measure the free play of the front brake lever at the lever end as shown in the figure.
- The free play of the brake lever before the engagement of brake should be between 15 ~ 20 mm.



Warning

Brakes are items of personal safety and should always be maintained in proper condition.



- 3. If the measured free play is more than the limit, adjust the nut provided at the front wheel end to obtain the correct play.
- 4. Turn the adjuster nut in clockwise direction for reducing the free play or turn it in anti-clockwise direction for increasing the free play.

Warning

Check the brake play periodically. However the brake play needs to be adjusted more frequently depending upon the usage.

TVS 🔀


Rear brake

- 1. Measure the free play of the rear brake pedal at the pedal end as shown in the figure.
- 2. The free play of the brake pedal before the engagement of brake should be between $15 \sim 20 \, \text{mm}$
- 3. If the measured free play is more than the limit, adjust the nut provided at the rear wheel end to obtain the correct play.
- 4. Turn the adjuster nut in clockwise to reduce the free play or turn it in anti-clockwise direction to increase the free play.





Brake shoe wear indicator





When the brake is applied, wear limit index mark (A) on both front and rear cam brake should be within the range of wear limit indicator (B) on panel assembly. Incase the index mark (A) is going beyond the wear limit (B), replace the brake shoes as a complete set, with the help of the nearest TVS Motor Company Authorised Main Dealer / Authorised Dealer. However, if cam lever adjustment goes beyond certain range, then index the cam lever to next slot (serration tooth) with the help of the nearest TVS Motor Company Authorised Main Dealer / Authorised Dealer, to utilize remaining shoe life until wear limit index mark (A) exceeds beyond the range of wear limit indicator (B).

•

Caution

Replace the brake shoes as a set, if wear limit index mark (A) exceeds beyond the range of wear limit indicator (B) even after indexing the lever.


BRAKES (SBT version)*

Front brake

- 1. Measure the free play of the front brake lever at the lever end as shown in the figure.
- 2. The free play of the brake lever before the engagement of brake should be between $15 \sim 20 \text{ mm}$.










Warning

Since the vehicle is fitted with Synchronised Braking Technologly (SBT) adjust the brakes with additional care. If not it may result in brakes not working properly.

Please contact TVS Motor Company Authorised Main Dealer or Authorised Dealer for any further assistance

- Turn the adjuster nut at bottom side (1) in the slot marked as "I" in clockwise direction for reducing the free play or in anti-clock wise direction for increasing the free play
- 4. After obtaining the necessary free play at the lever end, inspect for the clearance between the bullet (3) and slot end (4) marked as "S" as shown in figure.
- 5. If any clearance is found then turn the top side adjuster nut (2) at slot marked as "S" in clockwise direction until there is no clearance between the bullet (3) and slot top (4).






- 6. After adjusting the nut top, If any clearance is observed in between the bullet bottom (5) and slot bottom (6) marked as "I" as shown, then turn the adjuster nut (2) in anti-clockwise until the clearance is closed.
- 7. Once again check and confirm the brake play at the lever end.

Rear brake

- 1. Measure the free play of the rear brake pedal at the pedal end as shown in the figure.
- 2. The free play of the brake pedal before the engagement of brake should be between 15~20 mm.





Note

Please remember that the rear brake lever free play adjustment to be done only after adjusting the front brake lever play.

- If the measured free play is more than the limit, adjust the nut provided at the rear wheel end to obtain the correct play.
- Turn the adjuster nut clockwise to reduce the free play or turn it in anti-clockwise direction to increase the free play.




Brake shoe wear indicator(SBT version)

When the brake is applied, wear limit index mark (A) on both front and rear cam brake should be within the range of wear limit indicator (B) on panel assembly. Incase the index mark (A) is going beyond the wear limit (B), replace the brake shoes as a complete set, with the help of the nearest TVS Motor Company Authorised Main Dealer / Authorised Dealer. However, if cam lever adjustment goes beyond certain range, then index the cam lever to next slot (serration tooth) with the help of the nearest TVS Motor Company Authorised Main Dealer / Authorised Dealer, to utilize remaining shoe life until wear limit index mark (A) exceeds beyond the range of wear limit indicator (B).



Caution

Replace the brake shoes as a set, if wear limit index mark (A) exceeds beyond the range of wear limit indicator (B) even after indexing the lever.



TYRES

Tyre pressure:

Check the tyre pressure atleast once in a week if not more frequently. Insufficient air pressure in the tyres not only hasten tyre wear, but also seriously affects the stability of the vehicle.

Under inflated tyres make smooth cornering difficult and over inflated tyres decreases the tyre contact with the ground which can lead to skidding and loss of control. **Lower tyre pressure consumes more fuel**. Be sure that the tyre pressure is within the specified limit at all times.

MAINTENANCE



	Solo	Pillion
Front	1.75 kg/cm² (25 PSI)	1.75 kg/cm² (25 PSI)
Rear	2.00 kg/cm ² (28 PSI)	2.25 kg/cm² (32 PSI)

Tyre tread condition

Operating the vehicle with excessively worn tyres will decrease riding stability and can lead to loss of control. It is recommended to replace the tyre when the tyre wears off to the tyre wear indicator level (indicated by TWI on the tyre).

Tyre rotation direction



While reassembling the tyre, after removing from the wheel rim, ensure that the arrow mark (A) on the tyre facing the direction of wheel rotation.



Warning

The tyre inflation pressure in cold condition and the tyre tread condition are extremely important for the performance and safety of the rider. Check the tyres frequently for inflation pressure as well as the wear pattern on it. **Use of a tyre other than the standard may cause instability.**



DRIVE CHAIN

Proper lubrication and adjustment of drive chain gives long service life of chain. Poor maintenance of chain causes premature wear or damage to the drive chain and sprockets. Poor chain maintenance also affects mileage of the vehicle. The drive chain must be cleaned, checked, lubricated and adjusted at specified intervals mentioned in the maintenance schedule. If the vehicle is used under severe conditions and more dusty area, the drive chain must be attended more frequently.




Clean, check, lubricate and adjust the drive chain in the following manner:

- Place the vehicle on centre stand with the transmission in neutral
- 2. Remove the dust seal chain cover.
- 3. Inspect the drive chain slackness (vertical movement) using the finger as shown in the figure.
- The slackness of the drive chain should not exceed the limit (20 ~ 30 mm). Excess slackness consumes more fuel.
- If the slackness found more, contact TVS Motor Company Authorised Main Dealer / Authorised Dealer for adjustment.
- If the slackness found is within the limit, clean the chain with dry cloth and lubricate using TRU SPRAY/TRU4 oil.
- 7. Refit the dust seal chain cover.



FRONT WHEEL REMOVAL AND REASSEMBLY

- 1. Remove the axle nut (1) along with a washer.
- Pull out the axle (2) along with a washer and take out a spacer from the right side of the wheel
- 3. Place a support below the frame to prevent the vehicle from falling and lift the vehicle up.
- Dislocate the wheel assembly along with brake panel from the front fork. Separate the brake panel from the wheel and take out the wheel.



5. Reverse the procedure for reassembling. While reassembling ensure to locate the lug on fork leg L to the slot in the brake panel.

A


Warning


Always make sure that whenever the wheel is removed, axle nut is properly re-tightened to the specified torque.



REAR WHEEL REMOVAL AND REASSEMBLY

- Remove the rear brake adjuster nut (1) and disconnect the brake rod
- 2. Remove the split pin (2) and the nut (3) from the torque link mounting with the brake panel and disconnect the torque link.
- 3. Remove the axle nut (4).
- 4. Pull out the axle (5) and take out the spacer bush from the rear wheel assembly.





- 5. Tilt the vehicle to the left and take out the wheel along with the brake panel. Separate the brake panel from the wheel.
- 6. For locating and reassembling the rear wheel easily, engage the gear. This will arrest the free movement of the drum sprocket.
- 7. Reverse the procedure for reassembly.



Caution

Once the split pins are removed, replace them with new ones.



STORAGE PROCEDURES

For storage of your motorcycle for longer period of over a month and above, we recommend to carry out the following steps:

- Clean the vehicle thoroughly. Park the vehicle on centre stand.
- 2. Warm up the engine and drain engine cum transmission oil. Store the oil, if new, in a dust free container.
- 3. Empty the fuel tank. Turn the fuel cock lever to 'OFF' position.
- 4. Run the engine with fuel cock OFF position till the carburettor fuel bowl becomes empty.
- 5. Remove the spark plug and feed in several drops of engine cum transmission oil through spark plug hole. Crank the engine few times and reinstall the spark plug.

M Warning

The exhaust system becomes hot after a run. Park the vehicle in a place where pedestrians or children are not likely to touch the vehicle.

- 6. Remove the battery, store it away from direct sunlight and freezing temperatures.
- 7. Place a suitable support at the bottom of the frame so that both the tyres are off the ground. This will ensure better tyre life.
- 8. Cover up the vehicle completely with a clean tarpaulin or any other suitable cover. Store the vehicle inside a garage or similar area to avoid damage due to dust and rain. Make sure that the storage area is well ventilated and free from any source of flame or spark.

Caution

Do not park the vehicle on a slope or soft ground or else it may fall down. During storage, the battery must be recharged on a constant current battery charger at recommended amperage atleast once in a month.



TAKING THE VEHICLE OUT OF STORAGEFOR REGULARUSE

- Take the vehicle out of the garage and clean it thoroughly.
- Remount the battery after bench charging if required.
- Fill the engine cum transmission oil [TVS TRU4 PREMIUM oil (SAE 10W30 API-SL, JASO MA2)] and check the oil level using gauge oil level.
- 4. Lubricate the parts as instructed in the periodic maintenance schedule.
- 5. Fill up fresh petrol in the fuel tank.
- Check and inflate the tyres to the specified tyre pressure.
- 7. Check and correct the points mentioned in page no. 19.

Caution

Avoid using alkaline solution like detergent soaps for washing the vehicle. This may damage head lamp and other lamp assemblies.

8. Turn the ignition switch to 'ON' position. Start the engine with choke 'ON' for a few minutes and ride out

RECOMMENDED TIPS WHEN TAKING A LONG TRIP OF MORE THAN 500 KM:

- A) Please keep the following items for use in case of emergency:
 - 1. Tool kit.
 - 2. Recommended spark plug one number.
 - 3. Head lamp, tail lamp and turn signal lamp bulb one each.
 - 4. Throttle, clutch and front brake cable one each.
 - 5. Drive chain lock one number.
 - 6. First aid kit.
- B) Precautions to be taken for the journey:
 - Ensure engine cum transmission oil is up to the level.
 - 2. Adequate fuel in the fuel tank.



- C) Check your motorcycle for the following:
 - 1. Tightness of all bolts and nuts with correct torque value.
 - 2. Fitness of tyres/tyre pressure/tread depth.
 - 3. All bulbs, indicators and horn functioning.
 - 4. Smooth functioning of all the cables and their free plays.
 - 5. Smoothness of steering operation.
 - 6. Drive chain and sprocket condition. Chain adjustment.
 - 7. Front/rear brake functioning and rear brake lamp switch adjustment.
 - 8. Front fork for any abnormality.
 - 9. Fuel cock bowl filter cleanliness.
 - 10. Spark plug gap and condition of spark plug.
 - 11. Air filter elements cleanliness.
 - 12. Correct idling speed.



Warning

Long journey are to be taken only after the running-in period of 1000 km.

- 13. Lubrication of all items mentioned in the periodic maintenance schedule.
- 14. Intactness of EVAP system hoses and canister.
- 15. Any other job as necessary.
- Have your vehicle checked at any TVS Motor Company Authorised Main Dealer or Authorised Dealer.



TVS Motor Company Limited ('the Company') give this warranty with respect to the TVS Sport manufactured by the Company.

While the Company has taken every care to maintain quality in the manufacture of the TVS Sport, the above said warranty is subject to other terms of warranty:

During 5 Years from the date of purchase or during the first 60,000 km of run for the vehicle in the hands of original retail purchaser, whichever is earlier, the parts of the vehicle covered under warranty which prove to the satisfaction of the Company to have a manufacturing defect will be repaired or replaced free of cost.

The Company's obligation under this warranty is limited to repairing or replacing, free of cost, those parts of the vehicle which upon examination by the Company may prove to the Company's satisfaction to have a manufacturing defect, and in such cases the Company's decision either to repair or replace the affected parts will be final. In the event of replacement of parts, the Company also reserves the right to use parts of the same brand as the affected parts or any other brand which is used by the Company in the course of manufacture. All parts replaced under this warranty will become the property of the Company and must be returned to the company.

Limitations of Warranty:

This warranty shall not apply to following condition:

- 1. Any natural wear and tear, including without limitation, aging.
- 2. Warranty claims on proprietary items such as tyres, tubes and batteries etc,. should be preferred by the user directly on the respective manufacturer, as per their warranty terms and the Company shall not be liable in any manner in respect to the same.
- 3. Parts repaired or replaced under this warranty are warranted only throughout the remainder of the original warranty period.

- 4. The Company is not liable for any delay in servicing due to reasons beyond the control of the Company or any of its Authorised Main Dealers / Authorised Dealers.
- 5. In any event, the Company is not liable for indirect, remote, incidental or consequential damages.
- 6. The Company may make any modification or improvement to vehicles in future production at any time without prior notice and without any obligation to install the same on vehicles previously dispatched for sale.
- 7. Any claim under this warranty will lie only when the customer:
 - takes his vehicle to an Authorised Main Dealer / Authorised Dealer of the Company and reports the problem he / she felt in the vehicle to enable the Authorised Main Dealer / Authorised Dealer to inspect the same and assess the cause for the reported problems.
 - produces to such Authorised Main Dealer / Authorised Dealer the owner's manual for the concerned vehicle for verification of relevant details.
- 8. This is the only warranty given by the Company for the TVS Sport. No employee, Dealer or other person is authorised to extend or enlarge this warranty.

WARRANTY AND SERVICES

Warning

Modifications to this vehicle not approved by the TVS Motor Company may cause loss of performance and render it unsafe for use and disqualifies for warranty coverage also.

Following Toll Free numbers can be contacted for battery related queries if any.

Incase of EXIDE battery, call: 1800 103 5454 Incase of AMCO battery, call: 1800 425 0096



List of parts not covered under warranty

ITEM	WHAT TO CHECK FOR
Normal Maintenance operations	Engine tune-up, decarbonizing, fuel system cleaning, oil changes, head light focusing, fastener retightening, adjustments of carburettor, ignition timing, clutch and brakes as well as other normal adjustments.
Wear & tear items	Chain, sprockets, clutch and brake linings, fasteners, shims, washers, oil seals, gaskets, spokes etc.
Electrical	Bulbs , fuse, DRL
Service Maintenance Parts	Oil filters, spark plug, air filter, SAI filter, oil
Rubber, rexine & plastic items	All hoses , pipes and plastic aesthetics
Proprietary Items	Battery, tyres and tubes (the warranty terms are subject to our agreement with proprietary OEM)
	Parts of the vehicle getting affected due to atmospheric effect / environmental factors (rusting, paint peel off etc.). However, depending on the vehicle usage condition, warranty would be accepted up to 2 years from the date of purchase.
Others Factors	Parts of the vehicle which have been tampered with, altered, repaired or replaced by persons not authorised by the Company and which in the sole judgement of the Company affect the performance of the vehicle.
	Parts which are used in conjunction with parts not made or recommended by the Company.



List of parts not covered under warranty

ITEM	WHAT TO CHECK FOR
	Parts suffering damage or resultant damage by accident, misuse, negligent treatment, use of bad quality lubricants or impure fuel or by omission to follow the guidance and instructions contained in this owner's manual.
	Vehicles on which engine number or chassis number is deleted, defaced or altered.
Others Factors	Vehicles on which any warranty service including scheduled paid service is not availed when it falls due (at TVS Motor Company Authorised Main Dealer / Authorised Dealer).
	Vehicles sold or transferred by original retail purchaser.
	Vehicles used for racing or any competition or used otherwise than for ordinary personal transportation. Vehicles attached with side cars etc.
	Vehicles which have been taken out of India.
	Vehicles affected by natural calamities like flood, earthquake, tsunami, storm etc,.



Customer's Name and address
Frame number
Engine number
21191110 114111001
Key number
Service coupon no
Colour
Date of sale
Km
Registration number
Selling dealer's code, name, address and
phone number:

SERVICE INFORMATION

There are twenty one services for TVS Sport during warranty period. Of these, first four services are free services for which labour charges are free. In addition to these four free services, we have a scheme of seventeen pay services. Coupons for the free services are attached with this owner's manual. For keeping maintenance track of your vehicle, a pay service record sheet is also attached. Please have the record sheet filled by the Dealer who is carrying out the maintenance service.

Before you avail your first free service, please enter the particulars of your vehicle on the left side of this page. This will be useful for any reference.

For availing any of the twenty one warranty services, please take your vehicle and your owner's manual to any of our Authorised Main Dealer or any of our Authorised Dealer. After effecting the service the Authorised Main Dealer or the Authorised Dealer will take out the detachable portion of the relevant service coupon from your owner's manual for their records and will obtain your acknowledgment on the same for having the service done to your satisfaction. For your record, the Authorised Main Dealer or the Authorised Dealer will affix their stamp on the stub of the relevant service coupon or the last column of the record sheet whenever they carry out any service.

WARRANTY AND SERVICES



Periodic maintenance always helps good performance of an automobile and our services are planned to keep your TVS Sport performing good. Please note that carrying out the services for your vehicle at scheduled interval is necessary for availing of warranty. And please also remember that, after the services are over, periodic servicing of your vehicle at appropriate intervals, depending upon its extent of use, will keep your vehicle at its best level of performance.

In case you need any clarification or assistance, please feel free to write to us mentioning the frame number, engine number and the date of purchase of your vehicle also the name and place of the Authorised Main Dealer / Authorised Dealer from whom you bought the vehicle and getting it serviced.

Service Department
TVS MOTOR COMPANY LIMITED
P.O.Box No. 4, Harita, Hosur - 635 109,
TAMILNADU, INDIA.
Toll free no:- 1800-258-7111





Drive In.

Drive Out.



Say bye-bye to waiting time for servicing your bike.

Get your vehicle serviced in 1 hour at no additional cost. Contact your nearest Dealership for details.*





Busy Life? Easy Servicing!

Now, service your bike anywhere, anytime.

- ★ Service the vehicle at your door step.
- ★ Available for regular maintenance or breakdown service only.
- ★ Offered at nominal convenience charges.

Contact your nearest Dealership for details.*





Busy Life? Easy Servicing!

Now, Avail Pickup & Drop of your vehicle for service.

- ★ Vehicle picked up & delivered from/to your office or residence at prefixed appointed time.
- ★ Offered at nominal convenience charges.

Contact your nearest Dealership for details.*

TECHNICAL SPECIFICATIONS



MANUFACTURER : TVS MOTOR COMPANY LIMITED

P.B. No. 4, Harita, Hosur - 635 109, India.

ENGINE

Type : Single cylinder, 4 stroke, air cooled spark ignition engine

· 51 mm

Cylinder bore : 51 mm
Stroke : 48.8 mm
Piston displacement : 99.7 cc

Compression ratio : 9.40:1

Carburettor : Spaco AW PP

Air filter : Foam filter element Lubrication system : Forced oil pump

 $Maximum power in kW \quad : \quad 5.50 \, kW \, (7.48 \, PS) \, @ \, 7500 \, rpm$

Maximum torque in Nm : 7.5 Nm @ 5500 rpm

Maximum speed : Around 80 km/h

Engine idling rpm : $1500 \pm 200 \text{ rpm}$ (under warm

condition)

Starting system : Kick starter / electric starter*

Emission norms : BS IV

TRANSMISSION

Clutch : Wet - Multi plate type
Transmission : 4 speed constant mesh

Gear shift pattern : All up heel-toe shift

Primary transmission : Spur gears

Secondary transmission : Chain and sprockets

GEAR RATIOS

 I gear
 : 3.273

 II gear
 : 1.765

 III gear
 : 1.238

 IV gear
 : 0.958

 Primary reduction
 : 3.722

 Secondary reduction
 : 3.000

Applicable for electric start model only

TECHNICAL SPECIFICATIONS



CHASSIS

Overall length : 1950 mm
Overall width : 705 mm
Overall height : 1080 mm
Ground clearance : 172 mm

Wheel base : 1236 mm

Kerb weight (with toolkit

and 90% of fuel) : 106 kg (KS model)

: 108 kg (ES model)

Pay load : 130 kg

Maximum laden weight : 236 kg (KS model)

: 238 kg (ES model)

Steering angle : 88° Caster angle : 25.1°

Frame : Single cradle tubular frame Front suspension : Telescopic oil damped

Rear suspension : 5 step adjustable hydraulic

shocks with swing arm.

Trail length : 65 mm

TYRE

Tyre size
 Front : 2.75-17 41P 4PR
 Rear : 3.00-17 50P 6PR

Tyre pressure

Front : 1.75 kg/cm²(25 PSI) Rear-solo : 2.00 kg/cm²(28 PSI) Rear-dual : 2.25 kg/cm² (32 PSI)

BRAKES

Rear

Front : Hand operated, internally

expanding dia. 130 mm drum
: Foot operated, internally

expanding dia. 110 mm drum

ELECTRICAL

Type : AC generator
Ignition system : DC digital ignition
Spark plug : BOSCH UR4AC/

CHAMPION PRZ9HC

Spark plug gap : $0.6 \sim 0.8 \,\mathrm{mm}$

Magneto : 12V, 60W (fly wheel magneto)

Battery type : 12V, 2.5 Ah (KS model) : 12V. 5 Ah (ES model)

Body earthing : Negative terminal Head lamp : 12V.35/35W x 1

TECHNICAL SPECIFICATIONS



ELECTRICAL

Tail/brake lamp : 12V, 5/21W x 1
Turn signal lamp : 12V, 10W x 4
Speedometer lamp : 12V, 3.4W x 2
Fuel gauge lamp : 12V, 1.7W x 1
High beam indicator lamp : 12V, 1.7W x 1
Neutral indicator lamp : 12V, 1.7W x 1
Turn signal indicator lamp : 12V, 1.7W x 1

Economy and power

mode indicator lamps : 12V, 1.7W x 2 Horn : 12V, DC x 1 Fuse : 12V, 10A x 1

CAPACITIES

oil capacity

Fuel : **BS IV / Unleaded petrol**Fuel tank capacity : 10 liters (including reserve)**

Reserve : 2.0 liters

Engine cum transmission: TVS TRU4 PREMIUM oil

(SAE 10W30 API-SL, JASO MA2)

Engine cum transmission: 900 ml (after draining) and

1000 ml (after disassembly)
: Castrol / IOC teleshockab oil

Front fork oil grade : Castro
Front fork oil capacity : 155 ± 3

: 155 ± 2 ml per leg (GIL make) : 157 ± 2 ml per leg (TOP make) •

Caution

Using the bulb other than the specified rating can result in overloading of the electrical system or premature failure of the bulb.



Note

Specifications are subjected to change without notice.

** The fuel tank is not a measuring instrument and the capacity of fuel tank may slightly vary from the indicated capacity.



Dear Customer.

It is mandatory under the Motor Vehicles Act to insure all motor vehicles. No motor vehicle can be used in a public place without a valid policy of insurance issued by an authorised insurer. Driving a motor vehicle without any such insurance is an offense under Motor Vehicles Act.

To assist our customers on their insurance requirements such as the prompt issue and renewal of policies as well as expeditious settlement of claims if any, our preferred insurers are:





Regd. Office: Oriental House, A-25/27, Asaf Ali Road, New Delhi 110002

Website: www.orientalinsurance.nic.in



