





# The A-RT of Race Performance.

The all-new **Apache RACEEDITION 2.0** with 1st in segment Anti-Reverse Torque **Slipper Clutch.** 



**EUR** 4 | Dual-Channel ABS | FUEL INJECTED



# TVS APACHE RTR 200 4V FI SPECIFICATIONS

# FUEL INJECTED, TRACK FOCUSED FEATURES

#### **ENGINE**

Type 4S. Spark ignition Displacement 197.75 cm<sup>3</sup>

No. of Cylinders

Max. Engine Output (kW @ rpm) 13.70 kW @ 8500 rpm 16.96 Nm @ 6500 rpm Max. Torque (kW @ rpm)

66 mm Stroke 57.8 mm

**Fuel Injection** Bosch-Closed Loop

Bore to Stroke Ratio 1.14 Valve Per Cylinder 4 Valve Startina Electric Start Idle Speed 1550 ± 200 rpm

Mapped Ignition System Ignition

Power-to-Weight Ratio 0.089 kW/kg Compression Ratio 9.7 ± 0.5 : 1 Air Cleaner Type Viscous Paper Filter

Cooling System Oil Cooler with Ram Air Assist Twin Pipe and Twin Barrel Design Muffler

Wet Multi Plate clutch Clutch Gearbox Manual, 5-speed

#### **CHASSIS & SUSPENSION**

Double Cradle Split Synchro STIFF Frame

Telescopic with Hydraulic dampers Type / Description Spring

Front Suspension: Telescopic oil damped Rear Suspension: Gas charged Mono shock absorber,

7 step adjustable with rectangular swing arm

Shock Absorbers Front: Telescopic forks, Rear: Hydraulic

#### **ELECTRICAL**

Battery Ratina (Ah) 12V. 8 Ah MF Headlamp 12V, 60/55W, H4

#### **FUEL TANK CAPACITY**

Full 12±0.5 litre

#### **DIMENSIONS**

1080 mm Height Length 2070 mm Width 790 mm Wheelbase 1360 mm **Ground Clearance** 180 mm Saddle Height 810 mm

#### WHEEL & TYRE

90/90-17 M/C 49P Tubeless Tyre (front) Tyre (rear) 130/70-17 M/C 62P Tubeless

#### **BRAKE**

Front Ø270mm Disc Regr Ø240mm Disc Brake Fluid DOT3/DOT4

#### WEIGHT

Kerb weight with 90% 153.5 kg Fuel and Tool Kit 145 kg Dry Weight

#### **PERFORMANCE**

Max Speed 129 km/h in 5th gear

13.7 KW @ 8500 rpm Max. Engine output (kW @ rpm) Max. Torque (kW @ rpm) 16.96 Nm @ 6500 rpm

Acceleration

0-2sec (speed in km/h) 38 km/h 0-60km/h (time in sec)



#### Race-Derived O3C Tech

**Dual-Channel ABS** 

A New gen ABS unit -MAB100 HECU with special

development on the race track for superior braking

ABS with RLP (Rear wheel Lift-off Protection) control offers quick detection and recovery of the wheel lock

achieving higher stability through precise close-loop

and optimal cornering control. The Dual-Channel

algorithm is developed through extensive

Power ahead of the pack with oil-cooled combustion chamber technology and ram air-assisted cooling that reduces the engine heat map by 10°C. Harness explosive power from the high combustion Nanofriks coated piston.



### **Racing Double-Barrel Exhaust**

Fill the track with a racina roar thanks to a stainless steel exhaust that lets out the signature low frequency sound.



# First-in-segment Anti-Reverse **Torque Slipper Clutch**

The A-RT technology reduces back torque to a minimum allowing aggressive downshifts without experiencing wheel hopping. The 22% reduction in clutch force helps in quick launches and precise upshifts. enabling you to clock better lap times.







# Racing Origin Split Cradle Chassis

Carve up the track while having total control at high speeds and flex in tight corners.









#### AVAILABLE IN >





### Race-Tuned KYV Monoshock

Stay balanced through every corner, with a floating piston shock absorber, precision-tuned compression and rebound damping.

TVS MOTOR COMPANY













