

TVS
KARGO

TVS 



THE RIGHT BUSSINESS PARTNER

TABLE OF CONTENT

TVS Kargo Open Tray	2
-Specification	3
TVS Kargo Open Tray with Grill	4
-Specification	5
TVS Kargo Box	6
-Specification	7
TVS Kargo Moko	8
-Specification	9
Gallery	10



TVS KARGO OPEN TRAY
attachment dimension 1530mm x 1320mm x 475mm

SPEKIFIKASI



ENGINE

Engine Type	4 Stroke, SOHC
Engine Capacity	199,26 cc
Cylinder Arrangement	Single, Vertical
Maximum Power	6.40 kW @5250 rpm
Maximum Torque	14.95 Nm @3250 rpm
Bore x Stroke	62 mm x 66 mm
Fuel System	Carburator
Transmission	Manual 4 Speed, 1 Reverse
Clutch	Wet Multi Plate
Electrical System	DC-TCI
Starting System	Electric and Manual
Battery	MF - 12V 32Ah

FRAME


Length x Width x Height	2930mm X 1300mm X 1694mm
Wheel Base	1985 mm
Ground Clearance	158 mm
JBB / JBKB	645 Kg
Kerb Weight	380 Kg
Max Payload	265 Kg
Front Suspension	Trailing Arm Type
Rear Suspension	Trailing Arm Type
Front Brake	Hydrolic Drum Brake
Rear Brake	Hydrolic Drum Brake
Front Tyre Size	4.00 - 8 6PR
Rear Tyre Size	4.00 - 8 6PR

FUEL TANK

Fuel Capacity	7.5 Litre
Type of Fuel	Petrol

ATTACHMENT DIMENSION


Length x Width x Height	1530mm x 1320mm x 475mm
-------------------------	-------------------------



ENGINE

Engine with Duralife Technology produces more power, is durable and consumes less fuel.

Engine is designed exclusively for load carrying.



CHASIS / FRAME

Strong and rigid design. Able to carry heavy loads with stability and good maneuverability during riding.


Semi Monocoque Frame with Trailing Arm and suspension both in front and rear, give more stability, comfort and maneuverability.



CABIN

Comfortable for Driver. Roof protects driver from any weather condition

FITUR



DURALIFE ENGINE



LARGE CABIN



FUNCTIONAL DASHBOARD



MP3 PLAYER



COMBI BRAKE

ISO 9001 : 2015 certified

Tingkat Komponen Dalam Negeri (TKDN)

No. Tanda Sah
Sepeda motor roda tiga bak terbuka :
97/ILMATE/TKDN/1/2018

No. Tanda Sah
Sepeda motor roda tiga bak tertutup :
98/ILMATE/TKDN/1/2018



Deming Award Prize

Highest Award
in Total Quality
Management

* As a form of our commitment to product development, specifications are subject to change without prior notice



TVS KARGO OPEN TRAY WITH GRILL
attachment dimension 1495mm x 1260mm x 1060mm

SPEKIFIKASI

ENGINE

Engine Type	4 Stroke, SOHC
Engine Capacity	199,26 cc
Cylinder Arrangement	Single, Vertical
Maximum Power	6.40 kW @5250 rpm
Maximum Torque	14.95 Nm @3250 rpm
Bore x Stroke	62 mm x 66 mm
Fuel System	Carburator
Transmission	Manual 4 Speed, 1 Reverse
Clutch	Wet Multi Plate
Electrical System	DC-TCI
Starting System	Electric and Manual
Battery	MF - 12V 32Ah

FRAME

Length x Width x Height	2930mm X 1300mm X 1694mm
Wheel Base	1985 mm
Ground Clearance	165 mm
JBB / JBKB	645 Kg
Kerb Weight	404 Kg
Max Payload	250 Kg
Front Suspension	Trailing Arm Type
Rear Suspension	Trailing Arm Type
Front Brake	Hydrolic Drum Brake
Rear Brake	Hydrolic Drum Brake
Front Tyre Size	4.00 - 8 6PR
Rear Tyre Size	4.00 - 8 6PR

FUEL TANK

Fuel Capacity	7.5 Litre
Type of Fuel	Petrol

ATTACHMENT DIMENSION


Length x Width x Height	1495mm x 1260mm x 1060mm
-------------------------	--------------------------



ENGINE

Engine with Duralife Technology produces more power, is durable and consumes less fuel.

Engine is designed exclusively for load carrying.



CHASIS / FRAME

Strong and rigid design. Able to carry heavy loads with stability and good maneuverability during riding.


Semi Monocoque Frame with Trailing Arm and suspension both in front and rear, give more stability, comfort and maneuverability.



CABIN

Comfortable for Driver. Roof protects driver from any weather condition

FITUR



DURALIFE ENGINE



LARGE CABIN



FUNCTIONAL DASHBOARD



MP3 PLAYER



COMBI BRAKE

ISO 9001 : 2015 certified

Tingkat Komponen Dalam Negeri (TKDN)

No. Tanda Sah
Sepeda motor roda tiga bak terbuka :
97/ILMATE/TKDN/1/2018

No. Tanda Sah
Sepeda motor roda tiga bak tertutup :
98/ILMATE/TKDN/1/2018



Deming Award Prize

Highest Award
in Total Quality
Management

* As a form of our commitment to product development, specifications are subject to change without prior notice



TVS KARGO BOX
attachment dimension 1400mm x 1300mm x 1060mm

SPEKIFIKASI

ENGINE

Engine Type	4 Stroke, SOHC
Engine Capacity	199,26 cc
Cylinder Arrangement	Single, Vertical
Maximum Power	6.40 kW @5250 rpm
Maximum Torque	14.95 Nm @3250 rpm
Bore x Stroke	62 mm x 66 mm
Fuel System	Carburator
Transmission	Manual 4 Speed, 1 Reverse
Clutch	Wet Multi Plate
Electrical System	DC-TCI
Starting System	Electric and Manual
Battery	MF - 12V 32Ah

FRAME

Length x Width x Height	2996mm X 1350mm X 1795mm
Wheel Base	1985 mm
Ground Clearance	165 mm
JBB / JBKB	645 Kg
Kerb Weight	395 Kg
Max Payload	250 Kg
Front Suspension	Trailing Arm Type
Rear Suspension	Trailing Arm Type
Front Brake	Hydrolic Drum Brake
Rear Brake	Hydrolic Drum Brake
Front Tyre Size	4.00 - 8 6PR
Rear Tyre Size	4.00 - 8 6PR

FUEL TANK

Fuel Capacity	7.5 Litre
Type of Fuel	Petrol

ATTACHMENT DIMENSION


Length x Width x Height	1400mm x 1300mm x 1060mm
-------------------------	--------------------------



ENGINE

Engine with Duralife Technology produces more power, is durable and consumes less fuel.

Engine is designed exclusively for load carrying.



CHASIS / FRAME

Strong and rigid design. Able to carry heavy loads with stability and good maneuverability during riding.


Semi Monocoque Frame with Trailing Arm and suspension both in front and rear, give more stability, comfort and maneuverability.



CABIN

Comfortable for Driver. Roof protects driver from any weather condition

FITUR



DURALIFE ENGINE




LARGE CABIN



FUNCTIONAL DASHBOARD



MP3 PLAYER



COMBI BRAKE

ISO 9001 : 2015 certified

Tingkat Komponen Dalam Negeri (TKDN)

No. Tanda Sah
Sepeda motor roda tiga bak terbuka :
97/ILMATE/TKDN/1/2018

No. Tanda Sah
Sepeda motor roda tiga bak tertutup :
98/ILMATE/TKDN/1/2018



Deming Award Prize

Highest Award
in Total Quality
Management

* As a form of our commitment to product development, specifications are subject to change without prior notice



TVS KARGO MOKO

attachment dimension 1500mm x 1300mm x 1060mm

SPEKIFIKASI

ENGINE

Engine Type	4 Stroke, SOHC
Engine Capacity	199,26 cc
Cylinder Arrangement	Single, Vertical
Maximum Power	6.40 kW @5250 rpm
Maximum Torque	14.95 Nm @3250 rpm
Bore x Stroke	62 mm x 66 mm
Fuel System	Carburator
Transmission	Manual 4 Speed, 1 Reverse
Clutch	Wet Multi Plate
Electrical System	DC-TCI
Starting System	Electric and Manual
Battery	MF - 12V 32Ah

FRAME

Length x Width x Height	2996mm X 1250mm X 1795mm
Wheel Base	1985 mm
Ground Clearance	165 mm
JBB / JBKB	645 Kg
Kerb Weight	395 Kg
Max Payload	250 Kg
Front Suspension	Trailing Arm Type
Rear Suspension	Trailing Arm Type
Front Brake	Hydrolic Drum Brake
Rear Brake	Hydrolic Drum Brake
Front Tyre Size	4.00 - 8 6PR
Rear Tyre Size	4.00 - 8 6PR

FUEL TANK

Fuel Capacity	7.5 Litre
Type of Fuel	Petrol

ATTACHMENT DIMENSION


Length x Width x Height	1500mm x 1300mm x 1060mm
-------------------------	--------------------------



ENGINE

Engine with Duralife Technology produces more power, is durable and consumes less fuel.

Engine is designed exclusively for load carrying.



CHASIS / FRAME

Strong and rigid design. Able to carry heavy loads with stability and good maneuverability during riding.


Semi Monocoque Frame with Trailing Arm and suspension both in front and rear, give more stability, comfort and maneuverability.



CABIN

Comfortable for Driver. Roof protects driver from any weather condition

FITUR



ISO 9001 : 2015 certified

Tingkat Komponen Dalam Negeri (TKDN)

No. Tanda Sah
Sepeda motor roda tiga bak terbuka :
97/ILMATE/TKDN/1/2018

No. Tanda Sah
Sepeda motor roda tiga bak tertutup :
98/ILMATE/TKDN/1/2018



Deming Award Prize

Highest Award
in Total Quality
Management

* As a form of our commitment to product development, specifications are subject to change without prior notice

GALLERY



