





Proven 200cc Engine



Powerful. Fuel Efficient & Durable

3 Stage Air Filter



Extra Long Engine Life

Ventilated Tail Door



Better Cooling of Engine

Driver Footrest



More Comfort for the Driver

Easy Reverse Gear



Single Hand Operation

Twin Lockable Glove Box



Largest Storage - 5.8 ltrs.

Easy to Read Fuel Gauge



Accurate Fuel Quantity Display

Bluetooth Music System



Wireless Connection to Mobile Phone



TECHNICAL SPECIFICATIONS - TVS KING GS+

Type 4 Stroke, Single Cylinder Forced Air Cooled, Spark Ignition (SI) Engine

Displacement 199.26 cc

Max Power 7.5 kW @ 5500 rpm Max Torque 15.5 Nm @ 3250 rpm Engine Idling rpm 1200 ± 100 rpm **Electric & Hand Start** Starting Ignition DC Digital TCI

Fuel feed System UVD 18 Side Draft Carburetor -

Intake & Exhaust Valve Mechanism

Forced wet sump Lubrication

Magneto 12 V, 180 W @ 5000 rpm

TRANSMISSION

Type 4 Forward & 1 Reverse speed, Constant Mesh Fork and Cam Type

Shift mechanism

CHASSIS

Semi Monocoque Type

SUSPENSION

Front & Rear Trailing Arm Type Constant Rate Coil Spring with Co-Axial Hydraulic Damper

BRAKES

Front & Rear Hydraulic, Drum &

Automatic Adjuster Type

WHEELS & TYRES

3.00 D x 8 Rim size front & rear Tyre size front & rear 4.0 - 8, 6 PR

ELECTRICAL

Battery 12 V. 32 Ah

Head lamp 12 V, 35/35 W x 2, Twin head lamp

Tail / Stop lamp 12 V, 21/5 W x 2 Turn signal lamp 12 V, 10 W x 4 Reverse lamp 12 V. 21 W x 1

Low oil pressure & low fuel Warning lamp

12 V DC Horn

DIMENSIONS & WEIGHTS

Wheel base 1985 mm Wheel track 1150 mm Overall length 2647 mm Overall width 1329 mm Overall height 1740 mm Kerb weight 347 Kg Max laden weight 677 Kg

Ground clearance 194 mm (Unladen) / 165 mm

(Laden)

FUEL TANK CAPACITY

Petrol 10 liters

TVS Motor Company Ltd.

Post Box No. 4 Harita, Hosur - 635 109. Tel: 04344-276780. Fax: 04344-276878. www.tvsmotor.com